



E-1

Technical drawing of a Class A50-X road sign, showing front and side views with dimensions and angles.

Front View (Left):

- Overall width: 350 ± 20 mm
- Overall height: 420 ± 20 mm
- Top-left corner angle: $45^\circ \pm 0.5^\circ$
- Top-right corner angle: 80°
- Bottom-left corner angle: 45° min
- Top-left sloped edge length: $\text{max } 100$ mm
- Top-right sloped edge length: $\text{max } 250$ mm
- Left vertical edge length: $\text{min } 55 \text{ mm}$ to 140 mm
- Bottom-left sloped edge length: $\text{min } 65 \text{ mm}$
- Bottom-right sloped edge length: $\text{min } 65 \text{ mm}$
- Central circular hole diameter: $\phi 116 \pm 6$ mm
- Central circular hole position: 50 mm from the bottom edge

Side View (Right):

- Overall width: 350 ± 20 mm
- Overall height: 420 ± 20 mm
- Top-left corner angle: 45° max
- Top-right corner angle: 15° max
- Bottom-left corner angle: 30° max
- Bottom-right corner angle: 30° max
- Top-left sloped edge length: 100 max mm
- Top-right sloped edge length: 100 max mm
- Left vertical edge length: 75 ± 5 mm
- Bottom-left sloped edge length: 75 ± 5 mm
- Bottom-right sloped edge length: 75 ± 5 mm
- Central circular hole diameter: $\phi 116 \pm 6$ mm
- Central circular hole position: 50 mm from the bottom edge

Notes:

- Valný profil dle EU R-55.01
- Valný profil dle EU R-35.01

Legend:

- VOZOVKA

⚠

ISO 50

$\varnothing = 50\text{mm}$ ☒

$\varnothing > 49\text{mm}$ ☒

Tel.: +420 491421021
+420 491421022
mob.: +420 603360607
SVC GROUP ©- 05/19

QR kódem stáhnete rozšířený montážní návod / Com o código QR, você pode baixar as instruções de montagem estendidas