



E-1

Clase A50-X

The diagram illustrates the geometry for Class A50-X road markings, which are used for lane boundaries and center lines.

View A (Side View): Shows the profile of the marking. The vertical height of the marking is specified as $\text{max } 100$ mm and $\text{min } 65 \text{ mm}$. The horizontal distance from the edge of the pavement to the start of the marking is $\text{max } 250 \text{ mm}$. The angle of the marking relative to the horizontal is 8° . The width of the marking at its base is $\text{min } 55 \text{ mm}$ and $\text{max } 75 \text{ mm}$. The distance between the edges of the marking is $\text{min } 140 \text{ mm}$.

View B (Top View): Shows the plan view of the marking. The width of the marking is 350 ± 20 mm. The distance between the edges of the marking is $\text{min } 75 \text{ mm}$ and $\text{max } 100 \text{ mm}$. The angle of the marking relative to the horizontal is 39° max . The radius of the circular marking is $R = 55.01$ mm. The distance from the center of the circle to the edge of the pavement is $\text{min } 50 \text{ mm}$ and $\text{max } 75 \text{ mm}$. The distance from the center of the circle to the edge of the marking is $\text{min } 11.6 \text{ mm}$ and $\text{max } 16.6 \text{ mm}$.

⚠

ISO 50

$\varnothing = 50\text{mm}$ ☒

$\varnothing > 49\text{mm}$ ☒

Tel.: +420 491421021
+420 491421022
mob.: +420 603360607
SVC GROUP ©- 05/19

QR kódem stáhnete rozšířený montážní návod / Com o código QR, você pode baixar as instruções de montagem estendidas