



E-1

Technical drawing of a Class A50-X road sign, showing front and side views with dimensions and angles.

Front View (Left):

- Overall width: 350 ± 20 mm
- Overall height: 420 ± 20 mm
- Top-left corner angle: $45^\circ \pm 0.5^\circ$
- Top-right corner angle: 80°
- Bottom-left corner angle: 45° min
- Top horizontal edge: $\text{max } 100$ mm
- Left vertical edge: $\text{min } 55 \text{ mm}$ (with $\text{max } 140 \text{ mm}$ for the upper section)
- Bottom horizontal edge: $\text{min } 0.5 \text{ mm}$ (with $\text{max } 250 \text{ mm}$ for the lower section)
- Internal circular feature: $\phi 50 \text{ max}$
- Label: **A**

Side View (Right):

- Top horizontal edge: 100 max mm
- Top-right corner angle: 15° max
- Internal corner angle: 30° max
- Vertical edge: 75 min mm
- Bottom horizontal edge: 75 min mm
- Bottom-left corner angle: 30° max
- Internal circular feature: $\phi 16.6 \text{ max}$ (with $\phi 16.6 \text{ max}$ for the lower section)
- Label: **B**

Additional Information:

- Reference: **VOZOVKA**
- Text: **Valný protor die EJ R-55.01** (appearing twice)

⚠

ISO 50

$\varnothing = 50\text{mm}$ ☒

$\varnothing > 49\text{mm}$ ☒

Tel.: +420 491421021
+420 491421022
mob.: +420 603360607
SVC GROUP ©- 05/19

QR kódem stáhnete rozšířený montážní návod / Com o código QR, você pode baixar as instruções de montagem estendidas