



E-1

Technical drawing of a Class A50-X road sign, showing front and side views with dimensions and angles.

Front View (Left):

- Overall width: 350 ± 20 mm
- Overall height: 420 mm
- Top-left corner angle: $45^\circ \pm 0.5^\circ$
- Top-right corner angle: 8°
- Left side height: 140 ± 5 mm
- Left side width: 55 ± 5 mm
- Top horizontal distance: 100 mm (max)
- Bottom horizontal distance: 250 mm (max)
- Bottom-left corner angle: 45° min
- Bottom-left corner radius: $R = 55.01$ mm
- Bottom-left corner chamfer: 0.5 mm (min)
- Bottom-left corner chamfer: 0.5 mm (max)
- Bottom-left corner chamfer: 0.5 mm (min)
- Bottom-left corner chamfer: 0.5 mm (max)

Side View (Right):

- Overall width: 350 ± 20 mm
- Overall height: 420 mm
- Top-left corner angle: $45^\circ \pm 0.5^\circ$
- Top-right corner angle: 8°
- Left side height: 140 ± 5 mm
- Left side width: 55 ± 5 mm
- Top horizontal distance: 100 mm (max)
- Bottom horizontal distance: 250 mm (max)
- Bottom-left corner angle: 45° min
- Bottom-left corner radius: $R = 55.01$ mm
- Bottom-left corner chamfer: 0.5 mm (min)
- Bottom-left corner chamfer: 0.5 mm (max)
- Bottom-left corner chamfer: 0.5 mm (min)
- Bottom-left corner chamfer: 0.5 mm (max)

⚠

ISO 50

$\varnothing = 50\text{mm}$ ☒

$\varnothing > 49\text{mm}$ ☒

Tel.: +420 491421021
+420 491421022
mob.: +420 603360607
SVC GROUP ©- 05/19

QR kódem stáhnete rozšířený montážní návod / Com o código QR, você pode baixar as instruções de montagem estendidas