



E-1

Clase A50-X

The diagram illustrates the geometry for Class A50-X road markings, which are used for one-way traffic flow.

View A (Side View): Shows the profile of the marking. The vertical height of the marking is specified as $\text{max } 100$ mm and $\text{min } 65 \text{ mm}$. The horizontal distance from the edge of the pavement to the start of the marking is $\text{max } 250 \text{ mm}$. The angle between the marking surface and the horizontal is 8° . The angle between the marking surface and the vertical is $45^\circ \pm 0.5^\circ$. The width of the marking at its base is $\text{min } 55 \text{ mm}$ and $\text{max } 140 \text{ mm}$. The bottom edge of the marking is labeled "VOZOVKA".

View B (Top View): Shows the plan view of the marking. The width of the marking is 75 mm . The radius of the circular end of the marking is $R = 55.01$. The distance from the center of the circle to the edge of the pavement is 100 max . The angle between the marking surface and the horizontal is 39° max . The angle between the marking surface and the vertical is 45° min . The distance from the center of the circle to the edge of the pavement is 116.6 max .



 → $\varnothing = 50\text{mm}$ ☒

 → $\varnothing > 49\text{mm}$ ☒

Tel.: +420 491 421 021
+420 491 421 022
mob.: +420 603 360 607
SVC GROUP © - 05/19

QR kódem stáhnete rozšířený montážní návod / Com o código QR, você pode baixar as instruções de montagem estendidas