



E-1

Technical drawing of a Class A50-X road sign, showing front and side views with dimensions and angles.

Front View (Left):

- Overall width: 350 ± 20 mm
- Overall height: 420 mm
- Top-left corner angle: $45^\circ \pm 0.5^\circ$
- Top-right corner angle: 80°
- Bottom-left corner angle: 45° min
- Top horizontal edge: $\text{max } 100$ mm
- Left vertical edge: $\text{min } 55 \text{ mm}$ (total), 1.40 mm (segment)
- Bottom horizontal edge: $\text{min } 0.5 \text{ mm}$ (inner), $\text{max } 250 \text{ mm}$ (outer)
- Reference point A is located on the top horizontal edge.

Side View (Right):

- Top horizontal edge: 100 max mm
- Left vertical edge: 39° max
- Bottom-left corner angle: 39° max
- Bottom horizontal edge: 76 mm
- Inner vertical edge: 73 mm
- Inner corner angle: 40° max
- Inner horizontal edge: 50 mm
- Right vertical edge: $81.6 \pm 0.6 \text{ mm}$
- Right horizontal edge: $81.6 \pm 0.6 \text{ mm}$
- Reference point B is located at the bottom-right corner.

Notes:

- Valný profil dle EU R-55.01
- Valný profil dle EU R-35.01
- VOZOVKA



 $\varnothing = 50\text{mm}$ ☒

 $\varnothing > 49\text{mm}$ ☒

Tel.: +420 491421021
+420 491421022
mob.: +420 603360607
SVC GROUP ©- 05/19

QR kódem stáhnete rozšířený montážní návod / Com o código QR, você pode baixar as instruções de montagem estendidas